



COMMONWEALTH OF AUSTRALIA

***Ministerial Exemption Instrument No. 1 of 2013***

***Customs Tariff (Anti-Dumping) Act 1975***

I, MARK DREYFUS, Attorney-General, under subsection 8(7) of the *Customs Tariff (Anti-Dumping) Act 1975*, hereby exempt the goods described in Attachment 1 (the Goods) from:

- interim dumping duty; and
- dumping duty,

as I am satisfied that a Tariff Concession Order under Part XVA of the *Customs Act 1901* in respect of the good is in force.

This instrument commences on the 6th day of February 2013.

Dated this 25<sup>th</sup> day of July 2013.

MARK DREYFUS  
Attorney-General

**CURRENT Tariff Concession Orders (TCO) for tariff classification 7210.49.00**

All goods meeting at least one of the descriptions detailed below for the current TCOs are eligible for an exemption from dumping duties under Ministerial Exemption Instrument No. 1 of 2013.

**TC 1242989**

COILS, non-alloy steel, hot rolled, zinc coated, complying with American Society for Testing and Materials Standard ASTM A 653/A 653M - 05a, having ALL of the following:

- (a) coil thickness NOT less than 3.5 mm and NOT greater than 6.0 mm;
- (b) coil width NOT less than 784 mm and NOT greater than 1 263 mm;
- (c) minimum yield strength NOT less than 330 Mpa;
- (d) minimum tensile strength NOT less than 430 Mpa;
- (e) coil inside diameter NOT less than 711 mm and NOT greater than 813 mm;
- (f) zinc coating mass NOT less than 0.080 kg/m<sup>2</sup> per side;
- (g) each coil weighing NOT less than 14 metric tonnes;
- (h) chemical composition by weight of ALL of the following:
  - (i) carbon content NOT greater than 0.20%;
  - (ii) manganese content NOT less than 0.30% and NOT greater than 0.90%;
  - (iii) phosphorus content NOT greater than 0.03%;
  - (iv) sulphur content NOT greater than 0.03%;
  - (v) chromium content less than 0.30%;
  - (vi) molybdenum content less than 0.08%;
  - (vii) aluminium content NOT greater than 0.10%;
  - (viii) copper content NOT greater than 0.25%;
  - (ix) nickel content NOT greater than 0.25%;
  - (x) titanium content NOT greater than 0.04%;
  - (xi) vanadium content less than 0.10%;
  - (xii) silicon content NOT greater than 0.45%

Stated Use:

As raw material for the manufacture of Electric Resistance Welded (ERW) steel pipes and tubes

**TC 1317796**

COILS, non-alloy steel, hot rolled, zinc coated, complying with American Society for Testing and Materials Standard ASTM A 653/A 653M - 05a, having ALL of the following:

- (a) coil thickness NOT less than 1.48 mm and NOT greater than 6.0 mm;
- (b) coil width NOT less than 784 mm and NOT greater than 1 263 mm;
- (c) minimum yield strength NOT less than 360 Mpa;
- (d) minimum tensile strength NOT less than 460 Mpa;
- (e) coil inside diameter NOT less than 711 mm and NOT greater than 813 mm;

- (f) zinc coating mass NOT less than 0.080 kg/m<sup>2</sup> per side;
- (g) each coil weighing NOT less than 14 metric tonnes;
- (h) chemical composition by weight of ALL of the following:
  - (i) carbon content NOT greater than 0.20%;
  - (ii) manganese content NOT less than 0.50% and NOT greater than 1.00%;
  - (iii) phosphorus content NOT greater than 0.03%; (iv) sulphur content NOT greater than 0.03%;
  - (v) chromium content less than 0.30%;
  - (vi) molybdenum content less than 0.08%;
  - (vii) aluminium content NOT greater than 0.10%; (viii) copper content NOT greater than 0.25%;
  - (ix) nickel content NOT greater than 0.25%; (x) titanium content NOT greater than 0.04%;
  - (xi) vanadium content less than 0.1%;
  - (xii) silicon content NOT greater than 0.45%;

### **TC 0939596**

STEEL, COIL, hot dip zinc coated, complying with Japanese Industrial Standard JIS G 3302:2007, having ALL of the following:

- (a) yield strength NOT less than 275 N/mm<sup>2</sup> and NOT greater than 380 N/mm<sup>2</sup>;
- (b) tensile strength NOT less than 440 N/mm<sup>2</sup>;
- (c) elongation NOT less than 29% and NOT greater than 41%;
- (d) coating mass NOT less than 45 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup>;
- (e) thickness NOT less than 1.14 mm and NOT greater than 1.26mm;
- (f) width NOT less than 1 590 mm and NOT greater than 1 605 mm

Stated Use:

For the manufacture of motor vehicles

### **TC 1248929**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT greater than 210 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 40%;
- (d) total coating mass NOT less than 30 g/m<sup>2</sup> and NOT greater than 70 g/m<sup>2</sup> on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.75 mm and width 1 390 mm;
  - (ii) thickness 0.75 mm and width 1 450 mm;
  - (iii) thickness 0.75 mm and width 1 475 mm;
  - (iv) thickness 0.75 mm and width 1 530 mm;
  - (v) thickness 0.75 mm and width 1 565 mm;
  - (vi) thickness 0.75 mm and width 1 640 mm;
  - (vii) thickness 0.76 mm and width 1 220 mm;
  - (viii) thickness 0.80 mm and width 1 350 mm;
  - (ix) thickness 0.95 mm and width 820 mm;
  - (x) thickness 1.00 mm and width 624 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

### **TC 1248930**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 190 MPa;
- (b) tensile strength NOT less than 340 MPa;
- (c) total elongation NOT less than 32%;
- (d) total coating mass NOT less than 30 g/m<sup>2</sup> and NOT greater than 70 g/m<sup>2</sup> on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.70 mm and width 865 mm;
  - (ii) thickness 0.70 mm and width 980 mm;
  - (iii) thickness 0.70 mm and width 1 225 mm;
  - (iv) thickness 0.70 mm and width 1 244 mm;
  - (v) thickness 0.70 mm and width 1 300 mm;
  - (vi) thickness 0.70 mm and width 1 350 mm;
  - (vii) thickness 0.70 mm and width 1 370 mm;
  - (viii) thickness 0.70 mm and width 1 400 mm;
  - (ix) thickness 0.70 mm and width 1 410 mm;
  - (x) thickness 0.70 mm and width 1 455 mm;
  - (xi) thickness 0.70 mm and width 1 500 mm;
  - (xii) thickness 0.70 mm and width 1 585 mm;
  - (xiii) thickness 0.70 mm and width 1 710 mm;
  - (xiv) thickness 0.70 mm and width 1 720 mm;
  - (xv) thickness 0.65 mm and width 865 mm;
  - (xvi) thickness 0.65 mm and width 1 800 mm;
  - (xvii) thickness 1.00 mm and width 1 160 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

### **TC 1349350**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 165 MPa and NOT greater than 325 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 35% and NOT greater than 50%;
- (d) total coating mass NOT less than 45 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;
- (e) thickness 2.00 mm and width 1 070 mm

For the purposes of this Order, tolerances allowable for

specification (e) are:  
(a) thickness +/- 10%  
(b) width +/- 1%

### **TC 1349351**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 115 MPa and NOT greater than 305 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 37% and NOT greater than 57%;
- (d) total coating mass NOT less than 35 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.65 mm and width 870 mm;
  - (ii) thickness 0.65 mm and width 930 mm;
  - (iii) thickness 0.65 mm and width 1 150 mm;
  - (iv) thickness 0.65 mm and width 1 640 mm;
  - (v) thickness 0.65 mm and width 1 645 mm;
  - (vi) thickness 0.65 mm and width 1 680 mm;
  - (vii) thickness 0.65 mm and width 1 710 mm;
  - (viii) thickness 0.70 mm and width 925 mm;
  - (ix) thickness 0.70 mm and width 930 mm;
  - (x) thickness 0.70 mm and width 1 000 mm;
  - (xi) thickness 0.70 mm and width 1 005 mm;
  - (xii) thickness 0.70 mm and width 1 010 mm;
  - (xiii) thickness 0.70 mm and width 1 045 mm;
  - (xiv) thickness 0.70 mm and width 1 455 mm;
  - (xv) thickness 0.70 mm and width 1 485 mm;
  - (xvi) thickness 0.70 mm and width 1 550 mm;
  - (xvii) thickness 0.75 mm and width 1 135 mm;
  - (xviii) thickness 0.75 mm and width 1 140 mm;
  - (xix) thickness 0.75 mm and width 1 625 mm;
  - (xx) thickness 0.75 mm and width 1 670 mm;
  - (xxi) thickness 0.80 mm and width 1 060 mm;
  - (xxii) thickness 0.80 mm and width 1 150 mm;
  - (xxiii) thickness 0.80 mm and width 1 200 mm;
  - (xxiv) thickness 1.00 mm and width 1 610 mm;
  - (xxv) thickness 1.20 mm and width 1 595 mm;
  - (xxvi) thickness 2.30 mm and width 985 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1

### **TC 1349352**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 155 MPa and NOT greater than 295 MPa;
- (b) tensile strength NOT less than 340 MPa;
- (c) total elongation NOT less than 34%;
- (d) total coating mass NOT less than 35 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.70 mm and width 830 mm;
  - (ii) thickness 0.70 mm and width 855 mm;
  - (iii) thickness 0.75 mm and width 840 mm;
  - (iv) thickness 0.75 mm and width 855 mm;
  - (v) thickness 0.75 mm and width 1 630 mm;
  - (vi) thickness 0.75 mm and width 1 645 mm;
  - (vii) thickness 0.75 mm and width 1 683 mm;
  - (viii) thickness 0.75 mm and width 1 700 mm;
  - (ix) thickness 1.20 mm and width 1 170 mm;
  - (x) thickness 1.20 mm and width 1 175 mm;
  - (xi) thickness 1.20 mm and width 1 198 mm;
  - (xii) thickness 1.60 mm and width 1 160 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

#### **TC 1349354**

STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 235 MPa and NOT greater than 400 MPa;
- (b) tensile strength NOT less than 390 MPa;
- (c) total elongation NOT less than 28%;
- (d) total coating mass NOT less than 35 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 2.00 mm and width 975 mm;
  - (ii) thickness 2.30 mm and width 948 mm;
  - (iii) thickness 2.30 mm and width 1 030 mm;
  - (iv) thickness 2.30 mm and width 1 190 mm;
  - (v) thickness 2.60 mm and width 1 230 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%