



Heavy Vehicle National Law

Heavy Vehicle Stated Maps – Amendment Notice 2020 (No.2)

Statutory Instrument Series:

Stated Maps – Amendment Notice

1 Authorising provision

This Notice is made under:

- a) Section 174 of the Heavy Vehicle National Law as applied in each participating jurisdiction.

2 Purpose

The purpose of this Notice is to amend stated maps for vehicles at the request of road managers.

3 Commencement Date

The amendments take effect 28 days after publication of Amendment Notice 2020 (No.2)

4 Title

This Notice may be cited as the Heavy Vehicle Stated Maps – Amendment Notice 2020 (No.2)

5 Application

This Notice applies in all participating jurisdictions.

6 Amendments

The specified networks in Column 2 of Schedule 1 to this Notice are amended as specified in Column 4 for the Road Manager's reasons shown in Column 5.

Dated: 10 March 2020

Jose Arredondo
Manager Network Access
National Heavy Vehicle Regulator

Schedule 1: Table of Amended Routes

COLUMN 1 Authorising Provision	COLUMN 2 Network	COLUMN 3 Locality	COLUMN 4 Changes to Route	COLUMN 5 Road Manager Reasons for Change
s174 HVNL	Tasmania Tasmanian Class 1 Load Carrying Network	Heybridge	Add the following restriction for the combinations outlined in the Appendix A: <ul style="list-style-type: none"> • No access over SG 246 Blythe River Bridge (Westbound) on the Bass Highway 	Asset has been found to have issues with capacity for certain load carrying configurations
s174 HVNL	Tasmania Tasmanian Class 1 Load Carrying Network	Heybridge	Add the following condition for the combinations outlined in the Appendix B: <ul style="list-style-type: none"> • “Slow to and maintain a constant speed of 10 kilometres per hour” over SG 246 Blythe River Bridge (Westbound) on the Bass Highway 	Asset has been found to have issues with capacity for certain load carrying configurations

Appendix A

- **TLC 4-1a** – A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread quad-axle group with 4 tyres per axle.

Vehicle Designator		TLC4-1A			
Minimum		Maximum Axle Group Mass (t)			
Dolly Axles	Trailer Axles	Steer	Combined Drive	Trailer	Total
2.4	2.4	6.0	36.0	35.0	77.0
Note: Maximum dual-drive tandem axle group mass on prime mover for TLC4-1A is 18.5t					

- **TLC 4-2a** - A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a closed quad - axle group with 4 tyres per axle.

Vehicle Designator		TLC4-2A			
Minimum		Maximum Axle Group Mass (t)			
Dolly Axles	Trailer Axles	Steer	Combined Drive	Trailer	Total
2.4	2.4	6.0	36.0	30.0	72.0
Note: Maximum dual-drive tandem axle group mass on prime mover for TLC4-2A is 18.5t					

Appendix A (continued)

- **TLC 5-1a** – A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread tri - axle group with 8 tyres per axle.

Vehicle Designator		TLC5-1A			
Minimum		Maximum Axle Group Mass (t)			
Dolly Axles	Trailer Axles	Steer	Combined Drive	Trailer	Total
2.4	2.4	6.0	36.0	35.0	77.0
2.4	2.5	6.0	36.0	35.0	77.0
2.4	2.6	6.0	36.0	36.0	78.0
2.4	2.7	6.0	36.0	37.5	79.5
2.4	2.8	6.0	36.0	39.0	81.0
2.4	2.9	6.0	36.0	40.0	82.0
2.4	3.0	6.0	36.0	41.0	83.0
2.4	3.1	6.0	36.0	42.0	84.0
2.4	3.2	6.0	36.0	43.5	85.5
2.4	3.3	6.0	36.0	44.5	86.5
2.4	3.4	6.0	36.0	46.0	88.0
2.4	3.5	6.0	36.0	47.0	89.0

Note: Maximum dual-drive tandem axle group mass on prime mover for TLC5-1A is 18.5t

Appendix A (continued)

- **TLC 6-1a** – A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 8 tyres per axle and a low loader with a spread quad - axle group with 8 tyres per axle.

Vehicle Designator	TLC6-1A: Dolly axle group						
Minimum Ground Contact Width of Dolly Axles (m)	Maximum Dolly Axle Group Mass (t)						
	Minimum Distance from 2 nd to 5 th Axles (m)						
	4.8	5.0	5.2	5.4	5.6	5.8	6.0
2.4	21.0	22.0	22.0	22.5	23.0	23.0	23.0
2.6	22.0	22.0	22.5	23.0	23.0	23.5	24.0
2.8	22.0	22.5	23.0	23.0	24.0	24.5	25.0
3.0	22.5	23.0	23.0	24.0	25.0	25.5	26.0
3.2	23.0	23.0	24.0	25.0	26.0	26.5	27.0
3.4	23.0	24.0	25.0	26.0	27.0	28.0	28.5
3.6	24.0	25.0	26.0	27.0	28.0	29.0	29.5
3.8	25.0	26.0	27.0	28.0	29.0	30.0	31.0
4.0	26.0	27.0	28.0	29.0	30.0	31.0	32.0
4.2	27.0	28.0	29.0	30.0	31.0	32.0	33.0

Vehicle Designator	TLC6-1A: Trailer
Minimum Ground Contact Width of Trailer Axles (m)	Maximum Axle Group Mass of Trailer (t)
2.4	35.0
2.5	35.0
2.6	36.0
2.7	37.5
2.8	39.0
2.9	40.0
3.0	41.0
3.1	42.0
3.2	43.5
3.3	44.5
3.4	46.0
3.5	47.0

Appendix A (continued)

- **TLC 7-1a** – A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 8 tyres per axle and a low loader with a spread quad - axle group with 4 tyres per axle.

Vehicle Designator	TLC7-1A: Dolly axle group						
Minimum Ground Contact Width of Dolly Axles (m)	Maximum Dolly Axle Group Mass (t)						
	Minimum Distance from 2 nd to 5 th Axles (m)						
	4.8	5.0	5.2	5.4	5.6	5.8	6.0
2.4	21.0	22.0	22.0	22.5	23.0	23.0	23.0
2.6	22.0	22.0	22.5	23.0	23.0	23.5	24.0
2.8	22.0	22.5	23.0	23.0	24.0	24.5	25.0
3.0	22.5	23.0	23.0	24.0	25.0	25.5	26.0
3.2	23.0	23.0	24.0	25.0	26.0	26.5	27.0
3.4	23.0	24.0	25.0	26.0	27.0	28.0	28.5
3.6	24.0	25.0	26.0	27.0	28.0	29.0	29.5
3.8	25.0	26.0	27.0	28.0	29.0	30.0	31.0
4.0	26.0	27.0	28.0	29.0	30.0	31.0	32.0
4.2	27.0	28.0	29.0	30.0	31.0	32.0	33.0

Vehicle Designator	TLC7-1A: Combined Drive and Dolly axle groups						
Minimum Ground Contact Width of Dolly Axles (m)	Maximum Combined Drive and Dolly Axle Mass (t)						
	Minimum Distance from 2 nd to 5 th Axles (m)						
	4.8	5.0	5.2	5.4	5.6	5.8	6.0
2.4	35.0	36.0	37.0	38.0	39.0	39.5	40.0
2.6	36.0	37.0	38.0	39.0	40.0	40.5	41.0
2.8	37.0	38.0	39.0	40.0	41.0	41.5	42.0
3.0	38.0	39.0	40.0	41.0	42.0	42.5	43.0
3.2	39.0	40.0	41.0	42.0	43.0	43.5	44.0
3.4	40.0	41.0	42.0	43.0	44.0	45.0	45.5
3.6	41.0	42.0	43.0	44.0	45.0	46.0	46.5
3.8	42.0	43.0	44.0	45.0	46.0	47.0	48.0
4.0	43.0	44.0	45.0	46.0	47.0	48.0	49.0
4.2	44.0	45.0	46.0	47.0	48.0	49.0	50.0

Appendix A (continued)

Vehicle Designator	TLC7-1A: Trailer
Minimum Ground Contact Width of Trailer Axles (m)	Maximum Axle Group Mass of Trailer (t)
2.4	35.0

Appendix B

- **TLC2-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader with a spread quad axle group with 4 tyres per axle.

Vehicle Designator	TLC2-1A
Vehicle Designator	TLC2-1B

- **TLC2-2:** A single steer, dual-drive tandem axle group prime mover towing a low loader with a closed quad axle group with 4 tyres per axle.

Vehicle Designator	TLC2-2A
---------------------------	----------------

- **TLC3-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader with a spread quad axle group with 8 tyres per axle.

Vehicle Designator	TLC3-1A
Vehicle Designator	TLC3-1B

- **TLC4-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread quad-axle group with 4 tyres per axle.

Vehicle Designator	TLC4-1B
Vehicle Designator	TLC4-1C

- **TLC4-3:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread tri-axle group with 4 tyres per axle.

Vehicle Designator	TLC4-3A
Vehicle Designator	TLC4-3B

- **TLC4-4:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a closed tri-axle group with 4 tyres per axle.

Vehicle Designator	TLC4-4A
Vehicle Designator	TLC4-4B

Appendix B (continued)

- **TLC5-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread quad - axle group with 8 tyres per axle.

Vehicle Designator	TLC5-1B
Vehicle Designator	TLC5-1C

- **TLC5-3:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 4 tyres per axle and a low loader with a spread tri - axle group with 8 tyres per axle.

Vehicle Designator	TLC5-3A
Vehicle Designator	TLC5-3B

- **TLC6-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 8 tyres per axle and a low loader with a spread quad - axle group with 8 tyres per axle.

Vehicle Designator	TLC6-1B
Vehicle Designator	TLC6-1C

- **TLC6-3:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 8 tyres per axle and a low loader with a spread tri - axle group with 8 tyres per axle.

Vehicle Designator	TLC6-3A
Vehicle Designator	TLC6-3B

- **TLC7-1:** A single steer, dual-drive tandem axle group prime mover towing a low loader dolly with a tandem axle group with 8 tyres per axle and a low loader with a spread quad - axle group with 4 tyres per axle.

Vehicle Designator	TLC7-1B
Vehicle Designator	TLC7-1C