



Radiocommunications (Low Interference Potential Devices) Class Licence Variation 2003 (No. 1)

The AUSTRALIAN COMMUNICATIONS AUTHORITY makes this Variation under sections 132 and 134 of the *Radiocommunications Act 1992*.

Dated 31 July 2003

A.J SHAW
Chair

G.W LUTHER
Senior Executive Manager
Radiocommunications

Australian Communications Authority

1 Name of Variation

This Variation is the *Radiocommunications (Low Interference Potential Devices) Class Licence Variation 2003 (No. 1)*.

2 Commencement

This Variation commences on gazettal.

3 Variation of *Radiocommunications (Low Interference Potential Devices) Class Licence 2000*

Schedule 1 varies the *Radiocommunications (Low Interference Potential Devices) Class Licence 2000*.

Schedule 1 Variation

(section 3)

[1] Schedule 1, item 45

substitute

45	Digital modulation transmitters	915–928	1 W	<ol style="list-style-type: none">1. The radiated peak power spectral density in any 3 kHz is limited to 25 mW per 3 kHz.2. The minimum 6 dB bandwidth must be at least 500 kHz.
45A	Digital modulation transmitters	2400–2483.5	4 W	<ol style="list-style-type: none">1. The radiated peak power spectral density in any 3 kHz is limited to 25 mW per 3 kHz.2. The minimum 6 dB bandwidth must be at least 500 kHz.
45B	Digital modulation transmitters	5725–5850	4 W	<ol style="list-style-type: none">1. The radiated peak power spectral density in any 3 kHz is limited to 25 mW per 3 kHz.2. The minimum 6 dB bandwidth must be at least 500 kHz.